

1 WHAT IS CLAIMED IS

5

1. A liquid crystal display device,
comprising:

first and second, mutually opposing
substrates;

10 a liquid crystal layer confined between said
first and second substrates;

an electrode formed on said first substrate
so as to create an electric field acting generally
parallel to a plane of said liquid crystal layer; and

15 a plurality of pixels being defined in said
liquid crystal layer,

each of said plurality of pixels including
therein a plurality of domains having respective
orientations for liquid crystal molecules, such that
20 said orientation is different between a domain and
another domain within said plane of said liquid
crystal layer.

25

2. A liquid crystal display device as
claimed in claim 1, wherein each of said plurality of
pixels is formed in correspondence to said electrode,
30 said electrode comprising a first electrode and a
second electrode formed on said first substrate with a
mutual separation, said plurality of domains including
a first domain adjacent to said first electrode, a
second domain adjacent to said second electrode, and a
35 third domain intervening between said first domain and
said second domain, said liquid crystal molecules
aligning, in said first and second domains, in a first

1 direction forming a first angle with respect to a
direction of said electric field within said plane of
said liquid crystal layer, said liquid crystal
molecules aligning, in said third domain, in a second
5 direction forming a second angle with respect to said
direction of said electric field within said plane of
said liquid crystal layer, wherein said second angle
is larger than said first angle.

10

3. A liquid crystal display device as
claimed in claim 2, wherein said second angle is
15 larger than about 50° and smaller than about 75°.

20 4. A liquid crystal display device as
claimed in claim 2, wherein said first and second
electrodes extend parallel with each other, said first
and second directions being in a symmetric
relationship between a pair of mutually neighboring
25 pixels with respect to an elongating direction of said
first and second electrodes.

30

5. A liquid crystal display device as
claimed in claim 1, wherein said liquid crystal layer
has an initial resistivity of about $1 \times 10^{13} \Omega \text{cm}$ or
more.

35

1 6. A liquid crystal display device as
claimed in claim 5, wherein said liquid crystal layer
has a resistivity substantially smaller than said
initial resistivity.

5

 7. A liquid crystal display device,
10 comprising:
 first and second, mutually opposing
substrates;
 a liquid crystal layer confined between said
first and second substrates;
15 an electrode provided on said first
substrate so as to create an electric field acting
generally parallel to a plane of said liquid crystal
layer; and
 a spacer member disposed between said first
20 and second substrates,
 said liquid crystal layer being formed of a
liquid crystal having an initial resistivity of about
 $1 \times 10^{14} \Omega \text{cm}$,
 said spacer releasing an impurity to said
25 liquid crystal layer.

30 8. A liquid crystal display device as
claimed in claim 7, wherein said spacer carries an
epoxy resin on a surface thereof.

35

 9. A liquid crystal display device as

1 claimed in claim 7, wherein said liquid crystal layer
has an initial resistivity of about $1 \times 10^{13} \Omega \text{cm}$ or
more.

5

10. A liquid crystal display device as
claimed in claim 9, wherein said liquid crystal layer
10 has a resistivity substantially smaller than said
initial resistivity.

15

11. A liquid crystal display device,
comprising:

first and second, mutually opposing
substrates;

20 a liquid crystal layer confined between said
first and second substrates;

an electrode formed on said first substrate
so as to create an electric field acting generally
parallel to a plane of said liquid crystal layer; and

25 a plurality of pixels being defined in said
liquid crystal layer,

each of said plurality of pixels including a
plurality of domains having respective, mutually
different electro-optic properties.

30

12. A liquid crystal display device as
35 claimed in claim 11, wherein, in each of said pixels,
said electrode comprises an interdigital electrode
carrying a plurality of electrode fingers, said

1 plurality of electrode fingers being formed with an
interval which changes between an electrode finger
pair and a different electrode finger pair.

5

13. A liquid crystal display device as
claimed in claim 11, wherein said electrode comprises
10 an interdigital electrode carrying a plurality of
electrode fingers, an interval of said electrode
fingers being changed in each of said pixels.

15

14. A liquid crystal display device as
claimed in claim 11, wherein said electrode comprises
an interdigital electrode carrying a plurality of
20 electrode fingers, said plurality of electrode fingers
having respective, mutually different widths.

25

15. A liquid crystal display device as
claimed in claim 11, wherein said liquid crystal layer
has, in each of said plurality of pixels, a thickness
that changes in a direction perpendicular to a
30 direction of said electric field acting generally
parallel to said plane of said liquid crystal layer.

35

16. A liquid crystal display device as
claimed in claim 11, wherein said liquid crystal layer

1 comprises liquid crystal molecules such that said
liquid crystal molecules change an alignment direction
thereof in a direction generally perpendicular to a
direction of said electric field acting generally
5 parallel to said plane of said liquid crystal layer.

10 17. A liquid crystal display device as
claimed in claim 11, wherein said liquid crystal layer
comprises liquid crystal molecules such that said
liquid crystal molecules change a tilt angle thereof
in a direction generally perpendicular to a direction
15 of said electric field acting generally parallel to
said plane of said liquid crystal layer.

20 18. A method of fabricating a liquid
crystal display device, said liquid crystal display
device comprising: first and second, mutually opposing
substrates, a liquid crystal layer confined between
25 said first and second substrates, and an electrode
provided on said first substrate so as to create an
electric field acting generally in a plane of said
liquid crystal layer, said method comprising the step
of:

30 exposing a molecular alignment film formed
on each of said first and second substrates to a
polarized ultraviolet radiation.

35

19. A method as claimed in claim 18,

1 wherein said step of exposing said molecular alignment
film is conducted in a state that a plane of
polarization of said polarized ultraviolet radiation
coincides with a desired alignment direction of liquid
5 crystal molecules constituting said liquid crystal
layer.

10

20. A method as claimed in claim 18,
wherein said step of exposing said molecular alignment
film is conducted such that an exposure dose for a
non-pixel region is increased as compared with an
15 exposure dose for a pixel region.

20

21. A method of fabricating a liquid
crystal display device, said liquid crystal display
device comprising: first and second, mutually opposing
substrates, a liquid crystal layer confined between
said first and second substrates, and an electrode
25 provided on said first substrate so as to create an
electric field acting generally in a plane of said
liquid crystal layer, said method comprising the step
of:

introducing an impurity into said liquid
30 crystal layer.

35